

**Features:**

1. Stainless steel SS304, Full IP67 waterproof, M 16 metal waterproof connector.
2. Industrial 15" LCD panel, wide viewing angle, 350 nits brightness.
3. Adopt 5 wires resistive touch screen, high precision, durable, anti-interference. support touch with glove and with water.
4. Acid-resistant, alkali-resistant, corrosion-resistant. Anti glare and optical bonding are included
5. The front frame and rear shell are sealed with waterproof rubber strips, which can be disassembled for inspection and maintenance without affecting the waterproof performance
6. High performance motherboard, 7x24 continuous operation.

Model: SC15W**PC**

CPU	Intel® Core,i5-4288U,Quad core , Base 2.6 GHz, Turbo 3.1 GHz, Fanless
Memory	8GB DDR3 (4G, 16GB optional,)
Hard Drive Capacity	128G SSD
Hard Drive Optional	SSD: 256GB, 512GB
	HDD: 500GB,1TB
Graphics	Intel HD4400
Audio	Realtek ALC662HD
Network	1×Realtek 8111E,10/100/1000M
Wireless Network	Intel®Wi-Fi Link 5300 AGN
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian etc.

External I/O Ports

USB	2x IP67 USB2.0
LAN	1x IP67 RJ45
Power input	1×IP67 9-36V DC
Other	1×IP67 Power on/off button,WIFI

LCD panel

Panel size	15"
Display active area	304(W)×228(H) mm /11.968x8.976 in
Resolution	1024*768
Aspect ratio	4:3
Brightness (cd/m ²)	350 nits
Brightness control	PWM software to adjust brightness
Contrast ratio	700:1
View angle	80°/80°/70°/70° (R/L/U/D)
Support color	16.2M
Backlight	WLED, 50K hours

Touch panel	
Touchscreen Type	5 wire resistive touch
Surface Hardness	3H
Surface treatment	Anti glare
Luminousness	≥90%
Touch controller IC	EETI ETR400
Available touch drivers	Windows, Linux, Android, Mac
Touch bonding	Optical bonding
Power Supply	
Working voltage	DC 9-36V
Power consumption	26W
Power adapter	AC 100 ~ 240V input and DC +12V@7.5A MAX output, 90W
Enclosure	
Material	SS 304
Finish	Wire drawing
Color	Silver
Mounting	VESA mount 75/100mm
IP rating	Full panel IP67 waterproof
Cooling system	Passive - Fanless
Operating Environment	
Temperature Range	Operating: -20 to 70°C, storage :-30 to 80°C
Relative humidity	Up to 100% at all relevant temperatures, non-condensing
Vibration	GB/T 2423.10-2019
Shock	GB2423.5
EMC	Class B
Packing Details	
Product weight	Net weight 6kg / 13.227 lb Gross weight 8.5kg / 18.739 lb
Product dimension	368.7×293×58mm / 14.515x11.535x2.283 in
Packing info	1pcs/ctn 53×16×40cm / 20.866x6.299x15.748 in 8.5kg / 18.739 lb 2pcs/ctn 53×30×40cm / 20.866x11.811x15.748 in 17kg / 37.478 lb
Accessories	Power adapter, Power plug, Waterproof antenna, Waterproof LAN cable, Waterproof USB cable*2
Other	
Warranty	1 year warranty
Certificates	CE, FCC, RoHS