


Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. [Cover with 4mm glass AR glass, Anti glare, Anti UV.](#)
4. [1000cd/m2, sunlight readable, with light sensor for auto dimming.](#)
5. High performance motherboard, 7x24 continuous operation.
6. With wifi, bluetooth.
7. Android 7.1 system.

Model: SC215A
PC

CPU	RK3399, Dual Cortex-A72 + Quad Cortex-A53, 2.0GHz
Memory	4GB DDR3
Storage	16GB EMMC
GPU	ARM Mali-T860MP4 (600 MHz)
Decoding Resolution	Support 1080P
Operation System	Android 7.1
Play Modes	Support timing, loop and spots etc. play modes
Network Support	RJ45, WIFI, 3G, 4G, TD-LTE (optional)
Image Format	JPEG/BMP/GIF/PNG
Video Format	RMVB, FLV, MPEG1/2/4, AVI, WMV, MOV, MP4, TS, etc.
Audio Format	MP3, WMA, AAC, etc.
RTC Real Time Clock	YES

I/O Interfaces

USB	2xUSB
LAN	2xRJ45, 10M/100M adaptive ethernet
HDMI	1xHDMI , support 1080p
Card Slot	1x TF card slot
DC	1xDC
Phoenix terminal	1xPhoenix terminal

LCD panel

Panel size	21.5"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness	1000 cd/m², sunlight readable

Brightness control	Light sensor for auto dimming
Response time	30ms
Contrast ratio	1000:1
View angle	89°/89°/89°/89° (R/L/U/D)
Touch panel	
Touchscreen Type	10 point capacitive touch
	Cover with 4mm glass AR glass, Anti glare, Anti UV
Touch response time	<2ms
Luminousness	90%
Surface Hardness	7H
Working Life	>50 million times
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Appearance	Flat panel
Material	Aluminum alloy
Color	Black, Silver
VESA mounting	75x75mm/100x100mm
IP grade	Front IP65 waterproof
Operating Environment	
Working temperature	-20°C to 70°C
Storage temperature	-30°C to 80°C
Relative humidity	5-85% (npn-condensing)
Vibration resistance	5-19Hz/1.0mm amplitude, 19-200Hz/1.0g acceleration
Impact resistance	10g acceleration, 11ms period
Packing Details	
Net weight	7 kg
Gross weight	9 kg
Product dimension	53.7x32.85x4.8 cm
Packing size	73x45x19 cm
Accessories	Power adapter, power cord, Phoenix terminal cord
Other	
Mounting way	Embedded mounting screws (Optional)
	Wall mounting brackets (Optional)
	Desk stand holder (Optional)
Customization (optional)	3G, 4G, Webcam, RFID reader etc. Optional
Warranty	1 year warranty