Sihovision SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







Features:

- 1. IP67 sealed stainless steel enclosure including I/O, Sealed I/O with cable set included.
- 2. Industrial 15" LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt 5 wire resistive touch screen, high precision, durable, anti-interference. EETI waterproof solution, support touch with water and gloves.
- 5. Fanless design.
- 6. Acid-resistant, alkali-resistant, corrosion-resistant.
- 7. High performance motherboard, 7x24 continuous operation.

Model:SC15W PC CPU Intel® Celeron J1900, quad core, 2.0GHz, fanless Memory 8G DDR3 (2G, 4G Optional) Hard Drive Capacity 64G SSD SSD: 32G, 64G,128GB, 156G Hard Drive Optional HDD: 500GB, 1TB Graphics CPU Integrated graphics HD Graphics and support 1080p HD photo quality Audio Realtek ALC662, High Definition Audio (HD), Line in, Line out Network 1xRealtek RTL 8111E Gigabit Ethernet controller Wireless Network WIFI(Optional) 2*USB+2*LAN+ 2 RS232+1*DC power I/O Interface Operation System Support Windows 7/8/10, Linux, Ubuntu, Debian, etc. LCD panel 15" Panel size 1024*768 Resolution Aspect ratio 4:3 16.7M colors Support Color 400 nits Brightness (cd/m²) 5ms Response time 1000:1 Contrast ratio View angle 80°/80°/80°/80° (R/L/U/D) Touch panel Touchscreen Type 5 wire resistive touch Touch solution **EETI** waterproof solution Touch Interface **USB** <8ms Touch response time Luminousness 90% Surface Hardness 3H >35 million times Working Life Touch options (Capacitive touch optional)

Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤27W
Enclosure	
Material	Stainless steel 304
Color	Silver
IP grade	Full IP67 waterproof
Operating Environment	
Temperature Range	Operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	8.5 kg
Gross weight	9.7 kg
Product Dimension	38.7x31.1x8.1cm
Packing size	51×42×19 cm
Accessories	Waterproof power adapter, power cord, waterproof RS232/LAN/USB cable
Other	
Mounting way	Desk stand holder (Optional)
Warranty	1 year warranty
Certificate	CE, FCC, RoHS