



Features:

1. Full IP67 sealed stainless steel 304 enclosure, true flat panel design, round corner design.
2. With air valve, keep air pressure balance inside and outside, anti fogging.
3. Industrial LCD panel, wide viewing angle, high nits, true color.
4. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
5. EETI waterproof solution, touch can work well with drop water on screen.
6. Anti glare, Reduce ambient reflections and improve clarity.
7. optical bonding, Prevent condensation and fogging inside the screen and increase transmittance.
8. DC9~36V wide voltage.
9. Rounded corner guards designed to reduce safety hazards.
10. High performance motherboard, fanless design, 7x24 continuous operation.

Model: SC300S

PC	
CPU	Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, Fanless
CPU optional	Intel® Core i3-4010U Dual cores, Quad threads, Base 1.60GHz, fanless
CPU optional	Intel® Core,i5-4288U,Quad core , Base 2.6 GHz, Turbo 3.1 GHz, Fanless
CPU optional	Intel® Core i5-4300U, Dual Cores, Quad Threads, Base 1.9 Ghz, Turbo 2.9 Ghz, Fanless
CPU optional	Intel® Core i3-6157U Dual Cores Quad threads Base 2.40GHz, fanless
CPU optional	Intel® Core i5-6200U, Dual cores, Quad Threads, Turbo 2.8 GHz, Fanless
CPU optional	Intel® Core i5-8459U, Quad core, 8 Threads, Base 2.3 Ghz, Turbo 3.8 Ghz, Fanless
CPU optional	Intel® Core i5-1135G7, Quad core, 8 Threads, Turbo 4.2 Ghz, Fanless
Memory	8GB DDR4, (816GB 32GB optional,)
Hard Drive Capacity	128G BSSD
Hard Drive Optional	SSD: 256GB, 512GB, 1TB
	HDD: 500GB,1TB
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	Onboard Realtek RTL 8111E Gigabit Ethernet controller
I/O Interface	3*USB+1*LAN+1*RS232+1*DC
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian etc.
LCD panel	
Panel size	10.4"-21.5"
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m ²)	400 nits
Response time	10ms
Contrast ratio	1000:1
View angle	85/85/85/85 (R/L/U/D)
Touch panel	
Touchscreen Type	10 point capacitive touch
Touch Interface	USB (RS232 optional)
Touch response time	<8ms
Luminousness	90%
Surface Hardness	7H
Working Life	> 50 million times

Touch options	(5 wire resistive touch optional)
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	9~36V
Power consumption	≤45W
Enclosure	
Material	stainless steel case
Color	Silver
VESA mounting	100×100mm
IP-grade	Full IP65 waterproof
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Other	
Mounting (options)	1) provide wall bracket for wall-mounting, VESA 100×100mm
	2) provide stable metal holder to support the monitor
Certificates	CE, FCC, RoHs
Accessories	Power adapter, waterproof RS232/LAN/USB cable, power cord
Warranty	1 years warranty