


Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Brightness: 1000 nits, sunlight readable, Anti glare.
5. With dimmer to adjust brightness from 0 to 100%.
6. Ultra-thin front bezel 3mm, ideal for embedded mounting in outdoor kiosk/ parking machine/ charging station and so on.
7. High performance motherboard, 7x24 continuous operation.
8. Be with discrete graphics card: TGX1050

Model:SC185
PC

CPU	Intel® Core i5-6400, Quad Cores, Quad Threads, Base 2.7 GHz, Turbo 3.3 GHz
Memory	16G RAM
Hard Drive Capacity	256G SSD
Hard Drive Optional	SSD: 32G, 64GB, 256GB
	HDD: 500GB, 1TB
Graphics	Intel® HD Graphics 530
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI Optional
I/O Interface	2xUSB 3.0, 2xUSB 2.0, 2xCOM RS232,1x RJ45
	1xVGA/HDMI/Audio OUT/POWER DC
Graphics card	TGX1050
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.

LCD panel

Panel size	18.5"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	1000 nits, sunlight readable
Response time	5ms
Contrast ratio	1000:1
View angle	89°/89°/89°/89° (R/L/U/D)

Touch panel

Touchscreen Type	Project Capacitive Touch (10 points)
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times

Touch options	(5 wire resistive touch optional)
Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum Alloy bezel+high strong rolled steel back case
Color	Silver, Black, white, color can be customized
VESA mounting	75*75mm/100*100mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	Operating: -10 to 60°C, Storage: -20 to 70°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	6kg
Gross weight	8.1kg
Product Dimension	485×325×85mm
Packing size	69×55×20 cm
Accessories	Power adapter, power cord, embedded screws
Other	
Mounting (options)	Embedded mounting screws
	Wall mounting brackets (optional)
	Desk stand holder (optional)
Warranty	1 year warranty
Certificate	CE, FCC, RoHS

