


Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, EETI waterproof solution, Touch can work well with drop water on the screen.
4. Brightness: 1000 nits, sunlight readable, Anti glare.
5. Optical bonding solution.
6. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.
7. Ultra-thin front bezel 3mm, ideal for embedded mounting in outdoor kiosk/ parking machine/ charging station and so on.
8. High performance motherboard, 7x24 continuous operation.

Model:SC15

PC	
CPU	Intel® Core I3-4005U, dual core, 1.7GHz
Chipset	Intel ValleyView SSA-CUnit
Memory	8G DDR3 (2G, 4G optional)
Hard Drive Capacity	256G SSD
Hard Drive Optional	SSD: 32G, 64GB, 256GB
	HDD: 500GB, 1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI optional
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.
External I/O Ports	
USB	2xUSB3.0, 2xUSB2.0
LAN	1xRJ45
COM	2xRS232 (more optional)
Video Outputs	1xVGA, 1xHDMI
Audio	1 × 3.5mm Line-out, 1 × 3.5mm Line-in
Other	1xPower on/off button
LCD panel	
Panel size	15"
Display active area	304.128(W)×228.096(H) mm / 11.97 in × 8.98 in
Resolution	1024*768

Aspect ratio	4:3
Brightness (cd/m ²)	1000 nits sunlight readable
Brightness control	PMW software adjustment(Light sensor for auto dimming optional)
Contrast ratio	800:1
View angle	85°/85°/85°/85° (R/L/U/D)
Support Color	16.7M
Backlight	WLED, 50K hours
Touch panel	
Touchscreen Type	Projected Capacitive Touch (up to 10 points)
Surface Hardness	7H
Surface treatment	Anti glare (chemical etching)
Luminousness	≥85%
Touch controller IC	EETI 80
Available touch	Windows, Linux, Android, Mac, etc
Touch bonding	Air Bonding
Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V (DC 36V Optional)
Power consumption	≤40W
Power adapter	AC 100 ~ 240V input and DC +12V@5A MAX output, 60W
Enclosure	
Material	Aluminium alloy bezel+ Zinc Plating cold rolled steel rear housing+Aluminium alloy cooling
Finish	Front bezel, cooling fin: sandblasting+hard anodizing, UV-protection and Anti-discoloration
Color	Black
VESA mounting	VESA mount 75*75/100*100mm, Panel mount
IP grade	Front panel IP65 waterproof
Cooling system	Passive - Fanless
Operating Environment	
Temperature Range	operating: -20 °C (-4°F) to 70°C (158°F) , storage: -30 °C (-22°F) to 80°C (176°F)
Relative humidity	Up to 99% at all relevant temperatures, non-condensing
Vibration	GB/T 2423.10-2019
Shock	GB2423.5
EMC	Class B
Packing Details	
Product Weight	Net weight 5.2kg Gross weight 6.8 kg
Product Dimension	380×300×79mm
Packing info	1pcs/ctn 51×14×39cm 7 kg 2pcs/ctn 51×30×39cm 15 kg
Accessories	Power adapter, power cord, Wall mounting brackets
Other	
Warranty	1 year warranty

