

**Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD**

Professional Industrial panel PC/monitor manufacturer

Address: Room 607, 6/F, Building M, Feige Industry park, 1223 Guanguang Road , Longhua District, Shenzhen, China

Web: [www.sihovision.com](http://www.sihovision.com) Phone: +86 0755 23747569 Mobile: +86 13798532807 Email: [info@sihovision.com](mailto:info@sihovision.com)**Features:**

1. Aluminum alloy frame with sandblasting and oxidation process, anti-UV and anti-discoloration treatment, front shell IP65 waterproof
2. Industrial-grade LCD screen, full viewing angle, 1000 brightness visible under sunlight, automatic light sensor adjustment brightness
3. 10-point capacitive touch screen, the protective layer is 2mm tempered glass (chemically strengthened), the hardness reaches 7H, and the surface is treated with AG anti-glare treatment
4. EETI touch control solution, normal touch when there are water droplets on the touch screen
5. The touch screen and LCD screen are bonded using a full bonding process.
6. The PC is built with industrial-grade components, 7x24 continuous operation, wide operation temperature -20 to 70°C

**Model:SC07****PC**

CPU	Intel Core i3-10110U, Dual core , Frequency 2.1GHz, Turbo Frequency: 4.1GHz
Memory	8G DDR4 (16G, 32G Optional)
Hard Drive Capacity	128G SSD
Hard Drive Optional	SSD: 64G,256GB,512GB
	HDD: 500GB,1TB
Graphics	Intel Ultra HD Graphics 620
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1×RJ45
Wireless Network	WIFI Optional
I/O Interface	2×USB 2.0, 2×USB 3.0, 2 x COM RS232
	1×VGA/HDMI/RJ45/Audio/POWER DC
Operation System	Support Windows 10/11, Linux, Ubuntu, Debian etc.

**LCD panel**

Panel size	7"
Resolution	1024*600

Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m <sup>2</sup> )	400 nits
Response time	5ms
Contrast ratio	800:1
View angle	80°/80°/80°/80° (R/L/U/D)
<b>Touch panel</b>	
Touchscreen Type	Project Capacitive Touch (10 points)
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times
Touch options	( 5 wire resistive touch, IR touch optional)
<b>Power Supply</b>	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤35W
<b>Enclosure</b>	
Material	Aluminum Alloy
Color	Silver , Black, white, color can be customized
VESA mounting	75×75mm/100×100mm
IP grade	Front panel IP65 waterproof
<b>Operating Environment</b>	
Temperature Range	operating: -20 to 70°C, storage :-30 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
<b>Packing Details</b>	
Net weight	2.2kg
Gross weight	3kg
Product Dimension	TBD
Packing size	40x30x20cm
Accessories	Power adapter,embedded screws,user manual,warranty card
<b>Other</b>	
Mounting (options)	embedded mounting screws
	wall mounting brackets (optional)
	desk stand holder (optional)
Warranty	1 year warranty