Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







Features:

- 1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
- 2. Industrial LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
- 4. High performance motherboard, 7x24 continuous operation.
- 5. Integrated with RFID.
- 6. Support wall mounting, embedded mounting, desk stand mouting etc.

Model: SC104 PC Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, CPU **Fanless** Chipset Intel ValleyView SSA-CUnit 4G DDR4 (8G optional) Memory Hard Drive Capacity 128G SSD SSD: 64G, 128GB, 256GB Hard Drive Optional HDD: 500GB, 1TB Graphics CPU Integrated graphics HD Graphics and support 1080p HD photo quality Audio Realtek ALC662, High Definition Audio (HD), Line in, Line out Network 1xRealtek RTL 8111E Gigabit Ethernet controller Wireless Network WIFI 2xUSB 2.0, 1xCOM RS232 I/O Interface 1xVGA/HDMI/RJ45/Audio OUT/MIC IN/POWER DC Operation System Support Windows 7/8/10, Linux, Ubuntu, Debian, etc. LCD panel 10.4" Panel size 1024*768 Resolution Aspect ratio 4:3 Support Color 16.7M colors Brightness (cd/m²) 300 5ms Response time Contrast ratio 800:1 80°/80°/80°/80° (R/L/U/D) View angle

Touch panel	
Touchscreen Type Project Capacitive Touch (10 points)	
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times
Touch options	(5 wire resistive touch, IR touch optional)
·	(5 Wife resistive touch, IX touch optional)
Power Supply External Power Supply AC 100-240V	
Working voltage	DC 12V
Power consumption	≤21.5W
Enclosure	
Material	Aluminum Alloy
Color	Silver, Black, white, color can be customized
VESA mounting	75x75mm/100x100mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	Operating: -10 to 60°C, storage: -20 to 70°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	4kg
Gross weight	5kg
Product Dimension	36.26x23.5x6.6cm
Packing size	49x45x20cm
Accessories	Power adapter, embedded screws, user manual, warranty card
Other	
Mounting (options)	Embedded mounting screws
	Wall mounting brackets (optional)
	Desk stand holder (optional)
Warranty	1 year warranty
Certificate	CE, FCC, RoHS