



Features:

1. Made of sturdy and d case.
2. Industrial LCD panel
3. Fully sealed and fanl included.

4. Adopt multi-points P
Covered with 2mm tem

PC

CPU

Memory

Hard Drive Capacity
Hard Drive Optional
Graphics
Audio
Network
Wireless Network
I/O Interface
Operation System
LCD panel
Panel size
Resolution
Aspect ratio
Support Color
Brightness (cd/m ²)
Response time
Contrast ratio
View angle

Touch panel

Touchscreen Type

Touch Interface

Touch response time

Luminousness

Surface Hardness

Working Life

Touch options

Power Supply

External Power Supply

Working voltage

Power consumption

Enclosure

Material

Color

VESA mounting

IP grade

Operating Environment

Temperature Range

Relative humidity

Vibration

Packing Details
Net weight
Gross weight
Product Dimension
Packing size
Accessories
Other
Mounting (options)
Warranty
Certificate

SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Hongyi Building, No. 227, Fulian Area, Sanlian Community,
Longhua District, Shenzhen, China



Durable aluminum Alloy front bezel+304 Stainless steel back

High brightness, wide viewing angle, high nits, true color.

Rugged design, full IP66 waterproof, Sealed I/O with cable set

CAP touch panel, high sensitive and fast-response.
Tempered glass for vandalproof.

Model:SC32W

Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz,
Turbo 2.7 GHz, 4MB Cache, Fanless

4G DDR4 (2G, 8G optional)

128G SSD

SSD: 64G, 128GB, 256GB, 512GB, 1TB, 2TB

HDD: 500GB, 1TB

CPU Integrated graphics HD Graphics and support 1080p

Realtek ALC662, High Definition Audio (HD), Line in, Line

1xRealtek RTL 8111E Gigabit Ethernet controller

WIFI

1xUSB 2.0,1xUSB 1.0, 1xCOM RS232, 1xRJ45

1xHDMI/POWER DC 24V

Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.

32"

1920*1080

16:9

16.7M colors

400 (1000 nits, sunlight readable optional)

5ms

1400:1

80°/80°/80°/80° (R/L/U/D)

10 point capacitive touch

USB (RS232 optional)

<8ms

90%

7H

>50 million times

(5 wire resistive touch optional)

AC 100-240V

DC 24V

≤55W

Aluminum Alloy front bezel+304 Stainless steel back case

Silver, Black, white, color can be customized

100x100mm/200x200mm

Full IP66 waterproof

ment

operating: -20 to 70°C, storage: -30 to 80°C

5%~95% @ 40° C, non-condensing

5-500 Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis

TBD
TBD
82.9x52.3x9cm
TBD
Power adapter, waterproof HDMI/ RS232/LAN/USB cable,
wall mounting brackets
desk stand holder (optional)
1 year warranty
CE, FCC, RoHS