Sihovision SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional touchscreen monitor manufacturer

Address: Room 607, 6/F, Building M, Feige Industry park, 1223 Guanguang Road, Longhua District, Shenzhen, China Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: +86 13798532807 Email: info@sihovision.com





Features:

- 1. Fully enclosed design, the whole monitor is dustproof.
- 2. Seamless design flat bezel, front panel IP65 waterproof.
- 3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
- 4. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with touch glass for vandalproof.
- 5. High performance mainboard, 7x24 continuous operation.
- 6. VGA+HDMI+DVI interfaces, USB for touch.
- 7. EMI/ EMC standard Anti-electromagnetic interference.
- 8. Shock proof standard: GB2423. anti-static: 4KV-8KV. Anti surge.
- 9. With waterproof rubber seal on the back side.
- 10. Support wall mounting, desk stand, embedded mounting.

Model:SL27

LCD panel	
Panel size	27"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m²)	300+ (1000 nits Optional)
Contrast ratio	1000:1
View angle	89°/89°/89° (R/L/U/D)
Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points)
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch optional)
Signal Ports	
VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI

Audio in/out	Optional	
OSD		
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.	
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.	
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.	
Power Supply		
	AC 100-240V, 50-60Hz	
Working voltage	DC 12V (9-36V DC Optional)	
Power consumption	≤20W	
Enclosure		
Material	Aluminum Alloy	
Color	Black, Silver	
VESA mounting	100x100mm	
IP Grade	Front IP65 waterproof	
Operating Environment		
Temperature Range	Operating: -10 to 60°C, Storage: -20 to 70°C	
Relative humidity	Operating: 10% to 80%, Storage: 5% to 90%	
Packing Details		
Net weight	6kg	
Gross weight	8kg	
Product Dimension	320*269*61mm	
Packing size	74*45*18cm	
Accessories	Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card	
Other		
	Embedded mounting screws	
Mounting	Wall mounting brackets (Optional)	
	Desk stand holder (Optional)	
Warranty	1 year warranty	
Certificates	CE, FCC, RoHS	
Product Dimension		
	53	
	658 598	
336		

L