



SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional touchscreen monitor manufacturer

Address: Room 607, 6/F, Building M, Feige Industry park, 1223 Guanguang Road, Longhua District, Shenzhen, China

Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: +86 13798532807 Email: info@sihovision.com



Features:

1. Fully enclosed design, the whole monitor is dustproof.
2. Seamless design flat bezel, front panel IP65 waterproof.
3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
4. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with touch glass for vandalproof.
5. High performance mainboard, 7x24 continuous operation.
6. VGA+HDMI+DVI interfaces, USB for touch.
7. EMI/ EMC standard Anti-electromagnetic interference.
8. Shock proof standard: GB2423. anti-static: 4KV-8KV. Anti surge.
9. With waterproof rubber seal on the back side.
10. Support wall mounting, desk stand, embedded mounting.

Model:SL800M

LCD panel

Panel size	15.6"~43"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	350 nits
Contrast ratio	1000:1
View angle	89°/89°/89°/89° (R/L/U/D)

Touch panel

Touchscreen Type	Project Capacitive Touch (10 points)
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch optional)

Signal Ports	
VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI
Audio in/out	Optional
OSD	
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.
Power Supply	
External Power Supply	AC 100-240V, 50-60Hz
Working voltage	DC 12V (9-36V DC Optional)
Power consumption	≤20W
Enclosure	
Material	Aluminum Alloy
Color	Black, Silver
VESA mounting	100x100mm
IP Grade	Front IP65 waterproof
Operating Environment	
Temperature Range	Operating: -10 to 60°C, Storage: -20 to 70°C
Relative humidity	Operating: 10% to 80%, Storage: 5% to 90%
Accessories	Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card
Other	
Mounting	Embedded mounting screws
	Wall mounting brackets (Optional)
	Desk stand holder (Optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS