


Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, front IP65 waterproof and dustproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, high sensitive and fast-response.
4. High performance mainboard, 7x24 continuous operation.
5. Support wall mounting, embedded mounting, desk stand mouting etc.
6. Support video signal, power and touch over a single USB3.0 cable.

Model:SL101
LCD panel

Panel size	10.1"
Resolution	1280*800
Aspect ratio	16:10
Support Color	16.7M colors
Brightness (cd/m ²)	500 nits
Contrast ratio	800:1
View angle	85°/85°/85°/85° (R/L/U/D)

Touch panel

Touchscreen Type	Project Capacitive Touch (10 points)
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	> 50 million times
Touch options	(5 wires restive touch, IR touch optional)

Signal Ports

USB	1×USB (support video signal, power, and touch over a single USB3.0 cable)
-----	---

OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.

Power Supply

External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V
Power consumption	≤15W

Enclosure	
Material	aluminium alloy bezel+High strength cold rolled steel back case
Color	Black, Silver
VESA mounting	100x100mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	operating: -10 to 60°C, storage: -20 to 80°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	1kg
Gross weight	1.5kg
Product Dimension	25.7*17.5*2.75cm
Packing size	33*30*10cm
Accessories	USB3.0 cable
Other	
Mounting	embedded mounting screws
	wall mounting brackets (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS