

**Features:**

1. Open frame design.

Front bezel aluminum alloy brushed metal craft, seamless design, [front IP65 waterproof and dustproof](#).

2. Industrial LCD panel, wide viewing angle, high nits, true color.

3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.

4. EETI waterproof solution, touch function can work well with drop water on the screen.

5. [1000 nits, sunlight readable](#).

6. [Anti glare](#).

7. High performance mainboard, 7x24 continuous operation.

8. [Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C](#).

Model:SL156**LCD panel**

Panel size	15.6"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	1000 nits, sunlight readable
Brightness control	Light sensor for auto dimming
Contrast ratio	1000:1
View angle	80°/80°/80°/65° (R/L/U/D)

Touch panel

Touchscreen Type	Project Capacitive Touch (10 points)
Surface Treatment	Anti glare
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch, IR touch optional)

Signal Ports

VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI
Audio in/out	optional

OSD	
OSD control optional	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.
Power Supply	
External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum alloy bezel
Color	Black, Silver
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	1.9kg
Gross weight	3.8 kg
Product Dimension	41.5x24.5x3.32 cm
Packing size	49x35x18 cm
Accessories	Power adapter, power cord, USB touch cable, HDMI/ VGA cable.
Other	
Mounting	embedded mounting
Warranty	1 year warranty
Certificates	CE, FCC, RoHS