## Sihovision SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







## Features:

- 1. Front bezel aluminum alloy brushed metal craft, seamless design, front IP65 waterproof and dustproof.
- 2. Industrial LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
- 4. EETI waterproof solution, touch function can work well with drop water on the screen.
- 5.1000 nits, sunlight readable.
- 6. Anti glare.
- 7. High performance mainboard, 7x24 continuous operation.
- 8. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.
- 9. Support wall mounting, embedded mounting, desk stand mounting etc.

## Model:SL17

LCD panel	
Panel size	17"
Resolution	1280*1024
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m²)	1000 nits, sunlight readable
Brightness control	Light sensor for auto dimming
Contrast ratio	1000:1
View angle	80°/80°/80° (R/L/U/D)
Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points )
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 Optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch, IR touch optional)
Signal Ports	
VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI

Audio in/out	optional	
OSD		
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.	
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.	
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.	
Power Supply		
External Power Supply	AC 100 - 240V, 50-60Hz	
Working voltage	DC 12V	
Power consumption	≤35W	
Enclosure		
Material	Aluminum Alloy	
Color	Black, Silver	
VESA mounting	75×75mm/100×100mm	
IP grade	Front panel IP65 waterproof	
Operating Environment		
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C	
Relative humidity	operating: 10% to 80%, storage: 5% to 90%	
Packing Details		
Net weight	4.5kg	
Gross weight	6.5kg	
Product Dimension	42.74*35.6*7.65cm	
Packing size	53*47*18cm	
Accessories	Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card	
Other		
Mounting	embedded mounting screws	
	wall mounting brackets (optional)	
	desk stand holder (optional)	
Warranty	1 year warranty	
Certificates	CE, FCC, RoHS	