


Features:

1. The whole machine is made of 304 stainless steel, and front IP65 waterproof
2. Industrial-grade LCD screen, full viewing angle, 1000 brightness visible in the sun, with light sensor for auto adjusting the brightness
3. 10-point capacitive touch screen, the protective layer is 2mm tempered glass (chemically strengthened), the hardness reaches 7H, and the surface is AG anti-glare treatment
4. EETI touch control solution, normal touch when there are water droplets on the touch screen
5. Optical bonding between LCD and touch screen optional
6. Adopting industrial-grade components, 7x24 hours work, support wide temperature operation -20℃~70℃
7. Support wall mounting, embedded mounting, desk stand mounting etc.

Model:SL17
LCD panel

Panel size	17"
Display active area	337.92(W)x270.336(H) mm / 13.304x10.643 in
Resolution	1280*1024
Aspect ratio	5:4
Support Color	16.7M colors
Brightness (cd/m²)	1000 nits, sunlight readable
Brightness control	Light sensor for auto dimming optional
Contrast ratio	1000:1
View angle	85°/80°/80°/85° (R/L/U/D)
Support Color	16.7M
Backlight	WLED, 30K hours

Touch panel

Touchscreen Type	Projected Capacitive Touch (up to 10 points)
Surface Hardness	7H
Surface treatment	Anti glare (chemical etching)
Luminousness	≥85%
Touch controller IC	EETI 81
Available touch drivers	Windows, Linux, Android, Mac, etc
Touch bonding	Air bonding (Optical Bonding optional)
Touch optional	Resistive touch, IR touch, non touch optional

External I/O Ports

Video input	1×VGA, 1×DVI, 1×HDMI
Audio in/out	1×3.5mm Line-out, 1×3.5mm Line-in

Touchscreen interface	1×USB
Power connector	1×Screwable 9~36V DC jack
Power Supply	
Working voltage	DC 9~36V
Power consumption	30W
Power adapter	AC 100 ~ 240V input and DC +12V@5A MAX output, 60W
OSD	
Function Keys	5 Keys: Power/Menu/Up/Down/Return
Menu Functions	Brightness, Contrast, Screen Setting, Color Temp, OSD Language, Auto Adjust, Reset etc.
Support languages	English, Français, Español, Português, Deutsch, Italiano, Nederlands, Svenska, Suomi, Polski, čeština, Русский, 한국어, 日本語, 繁體中文, 简体中文
Enclosure	
Material	Stainless steel 304
Finish	Wire drawing
Color	Silver
Mounting	VESA mount 75*75/100*100mm
IP rating	Front panel IP65
Cooling system	Passive - Fanless
Operating Environment	
Temperature Range	Operating: -20 °C ~ 70°C (-4°F ~158°F) Storage: -30 °C~80°C (-22°F ~176°F)
Relative humidity	Up to 90% at all relevant temperatures, non-condensing
Vibration	GB/T 2423.10-2019
Shock	GB2423.5
EMC	Class B
Packing Details	
Product weight	Net weight 6.7kg
Product Dimension	422*354*46mm
Packing info	1pc/ctn 54*18*47cm 7.5kg 2pcs/ctn 55*34*48cm 16kg
Accessories	Power adapter, power cord, USB touch cable, HDMI/ VGA cable
Other	
Warranty	1 year warranty
Certificates	CE, FCC, RoHS
Product Dimension	

