

**Features:**

1. IP65 sealed stainless steel enclosure, Sealed I/O cables included.
2. Black Powder coated Housing with front OSD buttons.
3. Industrial LCD panel, wide viewing angle, true color.
4. 1000 nits high brightness, sunlight readable.
5. Covered with 3mm AF glass, anti-fogging, anti-fingerprint.
6. Interfaces: Video (BNC) & HDMI & DC12V (Power)
7. High performance motherboard, 7x24 continuous operation.

Model: SL215**LCD panel**

Panel size	21.5"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	1000 cd/m ² , sunlight readable
Contrast ratio	1000:1
View angle	89°/89°/89°/89° (R/L/U/D)
Customization	Covered 3mm Anti-fogging glass

Signal Ports

HDMI	1x HDMI
BNC	1x BNC
VGA	optional
Audio in/out	optional

OSD in the front bezel

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.

Power Supply

External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V
Power consumption	≤35W

Enclosure

Material	Stainless steel 304
Color	Black
VESA mounting	100x100mm

IP grade	Full IP66
Operating Environment	
Temperature Range	operating: -10 to 60°C, storage: -20 to 70°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	7KG
Gross weight	9 KG
Product Dimension	53.16*32.82*5.74cm
Packing size	65x45x19 cm
Accessories	IP66 waterproof Power adapter, Power cord, waterproof HDMI and BNC cables
Other	
Mounting	VESA mounting
	embedded mounting screws (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS

