



Features:

1. Open frame design, without case.
2. Industrial wide temperaturer LCD panel, wide viewing angle, high nits, true color.
3. 1000 nits high brightness, sunlight readable.
4. High performance mainboard, 7x24 continuous operation.
5. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.

Model:SL07

LCD panel

Panel size	7"
Resolution	1024*600
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	1000 nits, sunlight readable
Contrast ratio	800:1
View angle	85°/85°/80°/80° (R/L/U/D)

Signal Ports

VGA	1×VGA
HDMI	1×HDMI
DVI	optional
AV	optional
Audio in/out	optional

OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.

Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤10W
Enclosure	
Material	High strength cold rolled steel
Color	Black, Silver
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	0.8kg
Gross weight	1.3kg
Product Dimension	21.21x14.76x3.cm
Packing size	29x27x13cm
Accessories	Power adapter, Power cord, HDMI /VGA cable
Other	
Warranty	1 year warranty
Certificates	CE, FCC, RoHS