



Features:

1. Front bezel aluminum alloy brushed metal craft, seamless design, [front IP65 waterproof and dustproof](#).
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, high sensitive and fast-response.
4. EETI waterproof solution, touch function can work well with drop water on the screen.
5. [1000 nits, sunlight readable, with light sensor for auto dimming](#).
6. [Cover with 3MM AR glass, Anti UV, Anti glare, Antioxidation](#).
7. High performance mainboard, 7x24 continuous operation.
8. [Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C](#).
9. Support wall mounting, embedded mounting, desk stand mounting etc.

Model:SL15

LCD panel

Panel size	15"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m ²)	1000 nits, sunlight readable
Brightness control	Light sensor for auto dimming
Contrast ratio	1000:1
View angle	80°/80°/70°/70° (R/L/U/D)

Touch panel

Touchscreen Type	Project Capacitive Touch (10 points)
Surface Treatment	Anti glare
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch, IR touch optional)

Signal Ports

VGA	1x VGA
HDMI	1x HDMI
DVI	optional
Audio in/out	optional

OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.

Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.
Power Supply	
External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V
Power consumption	≤35W
Enclosure	
Material	Aluminum alloy bezel+High strength cold rolled steel back case
Color	Black, Silver
VESA mounting	75x75mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	4.5kg
Gross weight	6kg
Product Dimension	40x32x5.98cm
Packing size	47x44x18cm
Accessories	Power adapter, power cord, USB touch cable, HDMI/ VGA cable, embedded screws
Other	
Mounting	embedded mounting screws
	wall mounting brackets (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS

