Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







Features:

- 1. Front bezel aluminum alloy brushed metal craft, seamless design, front IP65 waterproof and dustproof.
- 2. Industrial LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
- 4. EETI waterproof solution, touch function can work well with drop water on the screen.
- 5.1000 nits, sunlight readable, with light sensor for auto dimming.
- 6. Anti glare.
- 7. High performance mainboard, 7x24 continuous operation.
- 8. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.
- 9. Support wall mounting, embedded mounting, desk stand mounting etc.

Model:SL185

LCD panel	
Panel size	18.5"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m²)	1000 nits, sunlight readable
Brightness control	Light sensor for auto dimming
Contrast ratio	1000:1
View angle	88°/88°/88° (R/L/U/D)
Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points)
Surface Treatment	Anti glare
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch, IR touch optional)
Signal Ports	
VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI
Audio in/out	optional
OSD	
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.

	,
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.
Power Supply	
External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum alloy bezel+ High strength cold rolled steel back case
Color	Black, Silver
VESA mounting	100x100mm
IP grade	Front panel IP65 waterproof
Operating Environme	ent
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 80%, storage: 5% to 90%
Packing Details	
Net weight	6.5 kg
Gross weight	7.5 kg
Product Dimension	48.48x30.54x3.8 cm
Packing size	64x46x18 cm
Accessories	Power adapter, power cord, USB touch cable, HDMI/ VGA cable, embedded screws open frame mounting kits
Other	
Mounting	embedded mounting screws
	wall mounting brackets (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS