Features:
1. Robust and durable 316 stainless steel enclosure, sealing design, full IP65 waterproof, Sealed I/O with cable set included.
2. 15" Industrial LCD panel, 1000 nits. sunlight readable.
3. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 3mm tempered glass for vandal-proof.
4. EETI waterproof solution, touch function can work well with drop water on the screen.
5. Optical boding.
6. Wide temperature range: operating: -20 to 70°C, storage: -30 to 80°C.
7. High performance mainboard, 7x24 continuous operation.
8. Wide voltage support: 9V-36V.

Model: SL15

LCD panel	
Panel size	15"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m²)	1000 cd/m², sunlight readable
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)
Customization	Covered 3mm tempered glass
Signal Ports	
VGA	1x VGA
HDMI	1x HDMI
DVI	optional
Audio in/out	optional
OSD in the front bezel	
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.
Power Supply	
External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	9V-36V
Power consumption	≤35W

Enclosure	
Material	316 Stainless steel
Color	Silver
VESA mounting	100x100mm
IP grade	Full IP65 waterproof
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 90%, storage: 5% to 90%
Packing Details	
Net weight	6 KG
Gross weight	7 KG
Product Dimension	36.47*38.9*5.8cm
Packing size	48x45x19 cm
Accessories	IP65 waterproof Power adapter, waterproof VGA/HDMI/USB touch cable
Other	
Mounting	VESA mounting
	embedded mounting screws (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS