


Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China.

Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com



Features:

1. Robust and durable aluminium alloy enclosure.
2. Industrial LCD panel, full viewing angle, high nits, true color.
3. Adopt 10 point capacitive touch screen, high precision, durable, anti-interference
4. High performance motherboard, 7x24 continuous operation.
5. Support wall mounting, embedded and rackmount etc.
6. With wifi, bluetooth. 5 mega-pixel camera, FRID, Fingerprint Reader. loudspeaker.
7. Suitable for prison application.

Model:SC101A

PC

CPU	RK3188, Cortex-A9 ,quad core, 1.6GHz
Memory	2G , (Max. 4G)
Storage	eMMC 8G , (Max. 16G)
Decoding Resolution	Support maximum 2048*1536
Operation System	Android 4.4.2
Play Modes	Support timing, loop and spots etc. play modes
Network Support	RJ45, WIFI, 3G, 4G , TD-LTE (optional)
Image Format	JPG/BMP/GIF/TIFF/PNG
Video Format	RMVB, FLV, MPEG1/2/4, AVI, WMV, MOV, MP4, TS etc.
Audio Format	MP3, WMA, AAC, etc.
RTC Real Time Clock	YES

I/O Interfaces

USB	2×USB (up to 5)
COM	2×COM
LAN	1×RJ45, 10M/100M adaptive ethernet
DC	1×DC
Card Slot	1×TF

LCD panel

Panel size	10.1"
------------	-------

Resolution	1366*768
Aspect ratio	16:9
Support Color	16.7M colors
Brightness	400 cd/m ²
Response time	5ms
Contrast ratio	800:1
View angle	89°/89°/89°/89° (R/L/U/D)
Touch panel	
Touchscreen Type	10 point capacitive touch
Touch response time	<2ms
Luminousness	90%
Surface Hardness	7H
Working Life	>50 million times
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum alloy
Color	Black, white, Silver , color can be customized
VESA mounting	75×75mm/100×100mm
Operating Environment	
Working temperature	-10°C to 55°C
Relative humidity	<85%
Vibration resistance	5-19Hz/1.0mm amplitude , 19-200Hz/1.0g acceleration
Impact resistance	10g acceleration , 11ms period
Packing Details	
Packing size	47×43×18 cm 4 kg
Accessories	Power adapter,embedded screws,warranty card, user manual
Other	
Customization	5 mega-pixel camera
	FRID
	Fingerprint Reader
	loudspeaker
Mounting (options)	1) provide wall brackets for wall-mounting, VESA 100×100mm
	2) provide stable metal holder to support the monitor
Customization	3G,4G,Webcam, RFID reader etc. optioanal
Warranty	1 year warranty