


Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China.

Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com**Features:**

1. Robust and durable aluminium alloy enclosure, front panel IP65 waterproof and dustproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt 10 point capacitive touch screen, high precision, durable, anti-interference
4. High performance motherboard, 7x24 continuous operation.
5. Support wall mounting, embedded and rackmount etc. apply to a wide range of industrial application.
6. With wifi, bluetooth, **5 mega-pixel webcam and RFID reader**.

Model:SC17A**PC**

CPU	RK3188,Cortex-A9 ,quad core,1.6GHz
Memory	2G , (Max. 4G)
Storage	eMMC 8G , (Max. 16G)
Decoding Resolution	Support maximum 2048*1536
Operation System	Android 4.4.2
Play Modes	Support timing, loop and spots etc. play modes
Network Support	RJ45, WIFI, 3G, 4G , TD-LTE (optional)
Image Format	JPG/BMP/GIF/TIFF/PNG
Video Format	RMVB,FLV,MPEG1/2/4,AVI, WMV, MOV, MP4, TS etc.
Audio Format	MP3,WMA,AAC,etc.
RTC Real Time Clock	YES

I/O Interfaces

USB	2×USB (up to 5)
COM	2×COM
LAN	1×RJ45, 10M/100M adaptive ethernet
HDMI	1×HDMI , support 1080p
DC	1×DC
Card Slot	1×TF

LCD panel

Panel size	17"
Resolution	1280*1024
Aspect ratio	4:3

Support Color	16.7M colors
Brightness	400 cd/m ²
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)
Touch panel	
Touchscreen Type	10 point capacitive touch
Touch response time	<2ms
Luminousness	90%
Surface Hardness	7H
Working Life	>50 million times
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Appearance	Flat panel
Material	Aluminum alloy
Color	Black, white, Silver , color can be customized
VESA mounting	75×75mm/100×100mm
IP grade	front IP65
Operating Environment	
Working temperature	-10°C to 55°C
Relative humidity	<85%
Vibration resistance	5-19Hz/1.0mm amplitude , 19-200Hz/1.0g acceleration
Impact resistance	10g acceleration , 11ms period
Packing Details	
Net weight	5.5 kg
Gross weight	6 kg
Product Dimension	TBD
Packing size	55×47×18 cm
Accessories	Power adapter,embedded screws,warranty card, user manual
Other	
Customization	RFID Reader
	Front 5 mega-pixel webcam
Mounting (options)	1) provide wall brackets for wall-mounting, VESA 100×100mm
	2) provide stable metal holder to support the monitor
Customization	3G,4G, reader etc. optioanal
Warranty	1 year warranty