## Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







## Features:

- 1. Fully enclosed design, front IP65 waterproof, fully dustproof.
- 2. Industrial LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt multi-points PCAP touch panel, covered with 2mm tempered glass for vandalproof.
- 4. High performance motherboard, 7x24 continuous operation.
- 5. Built-in RFID Reader(Dual frenquency 125khz 13.56MHz)
- 6. Support magnetic attraction on back base.
- 7. 24V DC

Model: SC121	
PC	
CPU	Intel® Core i3-6100U, dual core, 2.3GHz
Chipset	Intel ValleyView SSA-CUnit
Memory	4G DDR3
Hard Drive Capacity	32G SSD
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
I/O Interface	2xUSB 3.0, 2xRJ45, 1xVGA/HDMI/Audio OUT/POWER DC/Power button
	1xPhoenix terminal/Power switch button
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.
LCD panel	
Panel size	12"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m²)	400+
Response time	5ms
Contrast ratio	1000:1

Model: SC121

View angle	80°/80°/80° (R/L/U/D)	
Touch panel		
Touchscreen Type	Project Capacitive Touch (10 points)	
Touch Interface	USB (RS232 optional)	
Touch response time	2ms	
Luminousness	90%	
Surface Hardness	7H	
Working life	>50 million times	
Touch options	(5 wire resistive touch, IR touch optional)	
Power Supply		
External Power Supply	AC 100-240V	
Working voltage	DC 24V	
Power consumption	≤35W	
Enclosure		
Material	ABS+Aluminum alloy	
Color	Black, silver, white, color can be customized	
IP grade	Front panel IP65 waterproof	
Operating Environment		
Temperature Range	Operating: -10 to 60°C, storage: -20 to 80°C	
Relative humidity	5%~95% @ 40° C, non-condensing	
Vibration	5-500 Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis	
Packing Details		
Net weight	4.5kgs	
Gross weight	5.15kgs	
Product Dimension	34.96x24.96x7.6 cm	
Packing size	45x17x37CM	
Accessories	Power adapter, user manual, warranty card	
Other		
Mounting (options)	Embedded mounting	
	Wall mounting brackets (Optional)	
	Desk stand holder (Optional)	
Warranty	1 year warranty	
Certificate	CE, FCC, RoHS	