


**Features:**

1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof and dustproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt multi-points PCAP touch panel, high sensitive and fast-response.
4. High performance motherboard, 7x24 continuous operation.
5. Support wall mounting, embedded mounting, desk stand mouting etc.
6. With 2.0 mega-pixel Camera, Support infrared night vision function.
7. With finger print and RFID reader(125KHz).
8. WIFI(Intel AC7260HMW) and Bluetooth.

**Model:SC15**
**PC**

CPU	Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, Fanless
Chipset	Intel ValleyView SSA-CUnit
Memory	4G DDR4 (Max 8G)
Hard Drive Capacity	64G SSD(Samsung PM850 msata)
Hard Drive Optional	SSD: 32G, 128GB, 256GB
	HDD: 500GB, 1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1×Realtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI
I/O Interface	2×USB 3.0, 2×USB 2.0, 2 x COM RS232
	1×VGA/HDMI/RJ45/Audio OUT/MIC IN/POWER DC
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian etc.

**LCD panel**

Panel size	15"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors

Brightness (cd/m <sup>2</sup> )	300+
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)
<b>Touch panel</b>	
Touchscreen Type	Project Capacitive Touch (10 points)
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times
Touch options	(5 wire resistive touch, IR touch optional)
<b>Power Supply</b>	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤45W
<b>Enclosure</b>	
Material	Aluminum Alloy
Color	Silver , Black, white, color can be customized
VESA mounting	75×75mm/100×100mm
IP grade	Front panel IP65
<b>Operating Environment</b>	
Temperature Range	Operating: -10 to 60°C, storage :-20 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
<b>Packing Details</b>	
Net weight	6.5kgs
Gross weight	7kgs
Product Dimension	46×33.01×7.22cm
Packing size	60×42×20cm
Accessories	Power adapter, embedded screws, user manual, warranty card
<b>Other</b>	
Camera	Front 2.0 mega-pixel, Support infrared night vision function.
Customization	Finger printer and RFID reader(125KHz)
Mounting way	Embedded mounting screws
	Wall mounting brackets (Optional)
	Desk stand holder (Optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS