



Features:

1. Fully enclosed design, the whole PC is dustproof.
2. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
4. Industrial LCD panel, wide viewing angle, high nits, true color.
5. Adopt multi-points PCAP touch panel, high sensitive and fast-response. cover with 2mm tempered glass for vandalproof.
6. High performance motherboard, 7x24 continuous operation.
7. Integrated with emergency button on front bottom.

Model: SC19

PC	
CPU	Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, Fanless
Chipset	Intel ValleyView SSA-CUnit
Memory	4G DDR4 (8G optional)
Hard Drive Capacity	128G SSD
Hard Drive Optional	SSD: 32G, 128GB, 256GB
	HDD: 500GB, 1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI
I/O Interface	3xUSB 2.0, 1xUSB 3.0, 2xCOM RS232
	1xVGA/HDMI/RJ45/Audio OUT/MIC IN/POWER DC
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.
LCD panel	
Panel size	19"
Resolution	1280*1024
Aspect ratio	5:4
Support Color	16.7M colors

Brightness (cd/m²)	300+
Response time	5ms
Contrast ratio	1000:1
View angle	85°/85°/80°/85° (R/L/U/D)
Touch panel	
Touchscreen Type	Project Capacitive Touch (10 points)
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50 million times
Touch options	(5 wire resistive touch, IR touch optional)
Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤35W
Enclosure	
Material	Aluminum Alloy
Color	Silver, Black, white, color can be customized
VESA mounting	75x75mm/100x100mm
IP grade	Front panel IP65 waterproof
Operating Environment	
Temperature Range	Operating: -10 to 60°C, Storage: -20 to 70°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	8.15kgs
Gross weight	10.35kgs
Product Dimension	44.9x45.9x12.2cm
Packing size	63x52x25cm
Accessories	Power adapter, embedded screws, user manual, warranty card
Other	
Mounting (options)	Embedded mounting screws
	Wall mounting brackets (Optional)
	Desk stand holder (Optional)
Warranty	1 year warranty
Certificate	CE, FCC, RoHS