Sihovision® SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







Features:

Aspect ratio

4:3

- 1. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof and dustproof.
- 2. Industrial LCD panel, wide viewing angle, high nits, true color.
- 3. Adopt multi-points PCAP touch panel, high sensitive and fast-response
- 4. High performance motherboard, 7x24 continuous operation.
- 5. Support wall mounting, embedded mounting, desk stand mouting etc.
- 6.Customized with Double-sided screen, PC integrated with speaker,RFID,fingerprinter reader.

Model:SC19 Windows PC Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, **CPU Fanless** Chipset Intel ValleyView SSA-CUnit 4G DDR4, (Max. 8G) Memory Hard Drive Capacity 128G SSD SSD: 64G,128GB,256GB Hard Drive Optional HDD: 500GB,1TB Graphics CPU Integrated graphics HD Graphics and support 1080p HD photo quality Realtek ALC662, High Definition Audio (HD), Line in, Line out Audio 1×Realtek RTL 8111E Gigabit Ethernet controller Network Wireless Network WIFI 4×USB 2.0, 1×RJ45,1×POWER DC I/O Interface Operation System Support Windows 7/8/10, Linux, Ubuntu, Debian etc. LCD panel (Double-sided screen) 19" Panel size Resolution 1280*1024

Support Color	16.7M colors
Brightness (cd/m²)	400+
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80° (R/L/U/D)
Touch panel	
Touchscreen Type	10 point capacitive touch
Touch response time	<2ms
Luminousness	90%
Surface Hardness	7H
Working Life	>50 million times
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum Alloy
Color	Silver , Black, white, color can be customized
IP grade	front panel IP65 waterproof
Operating Environment	
Temperature Range	operating: -10 to 60°C, storage :-20 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	7.5kg
Gross weight	9kg
Product Dimension	TBD
Packing size	74×45×18 cm
Accessories	Power adapter,user manual,warranty card
Other	
Customization	Speaker
	RFID
	Fingerprint Reader
	desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE,FCC,RoHS