



## Features:

1. Stainless steel enclosure, true flat panel design, front panel IP66 waterproof.
2. Industrial LCD panel, wide viewing angle, high nits, true color.
3. Adopt high sensitive multi-points PCAP touch panel, covered with 2mm tempered glass for vandalproof.
4. High performance motherboard, 7x24 continuous operation.
5. [Integrated with magnetic stripe card reader for customer identification](#)
6. RS232 convert to RJ45 (10pins) ports

## Model:SC15

### PC

CPU	Intel® Core I7-4500u, quad core, 1.8GHz, fanless
Memory	8G
Hard Drive Capacity	512G SSD
Hard Drive Optional	SSD: 32G, 64G, 128GB, 256GB
	HDD: 1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Network	1xRealtek RTL 8111E Gigabit Ethernet controller
Wireless Network	WIFI
I/O Interface	2xUSB 2.0, 2xUSB 3.0, <a href="#">4xCOM RS232(convert to RJ45)</a>
	1xVGA/HDMI/RJ45/Audio OUT/MIC IN/POWER DC
Card Reader	<a href="#">Magnetic stripe card for customer identification</a>
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian, etc.

### LCD panel

Panel size	15"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m <sup>2</sup> )	400
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)

Touch panel	
Touchscreen Type	10 point capacitive touch
Touch Interface	USB (RS232 optional)
Touch response time	<8ms
Luminousness	90%
Surface Hardness	7H
Working Life	>50 million times
Touch options	( 5 wire resistive touch optional)
Power Supply	
External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Stainless steel
Color	Silver, Black, white, color can be customized
VESA mounting	100x100mm
IP grade	Front panel IP66 waterproof
Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -20 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	7.5kg
Gross weight	9 kg
Product Dimension	43.17x30.7x6.27cm
Packing size	47x43x18cm
Accessories	Power adapter, embedded screws, user manual, warranty card
Other	
Mounting (options)	wall mounting brackets (optional)
	desk stand holder (optional)
Warranty	1 year warranty
Certificate	CE, FCC, RoHS