



Features:

1. Full sealed and fanless design , IP65 waterproof , used as a Time and Attendance device in factory.
2. Industrial LCD panel, 1000cd/m² sunlight readable , auto adjust brightness
3. High sensitive 10-points PCAP touch panel , cover with 3mm tempered glass, vandalproof
4. High performance motherboard, 7x24 continuous operation.
5. 4G/3G + WIFI + 5 million pixels webcam + Fingerprint Reader
6. Built-in Battery, 9000mah, keep the PC running for 3 hours in case power cut
7. Access to SSD/ Sim Card by removable panel.

Model:SC15

PC

CPU	Intel® Celeron J4125, 4 Cores, 4 Threads, Base 2.0 GHz, Turbo 2.7 GHz, 4MB Cache, Fanless
Chipset	Intel ValleyView SSA-CUnit
Memory	4G DDR4
Hard Drive Capacity	128G SSD
Hard Drive Optional	SSD: 16GB,32GB,64GB,128GB,160GB
	HDD: 160GB,320GB,500GB,1TB
Graphics	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
Audio	Realtek ALC662, High Definition Audio (HD), Line in, Line out
Ethernet	2×Realtek RTL 8111E Gigabit Ethernet controller
Wireless	4G/3G + WIFI
Webcam	5 million pixels webcam
Fingerprint Reader	Lumidigm V310 (optional)
Built-in Battery	9000mah, keep the PC running for 3 hours in case power cut , uninterruptible power supply
I/O Interface	1×Power AC, 2×LAN, 3×USB
Operation System	Support Windows 7/8/10, Linux, Ubuntu, Debian etc.

LCD panel

Panel size	15"
Resolution	1024*768
Aspect ratio	4:3

Support Color	16.7M colors
Brightness	1000 cd/m ² , with light sensor , auto adjust brightness
Response time	5ms
Contrast ratio	1000:1
View angle	80°/80°/80°/80° (R/L/U/D)
Touch panel	
Touchscreen Type	10-points Project Capacitive Touch Panel
Tempered glass cover	3mm
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
Working life	>50million times
Touch options	(4/5 wires resistive touch, IR ,SAW touch optional)
Power Supply	
External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤45W
Enclosure	
Material	Aluminum Alloy front bezel + High strength cold rolled steel back case
Color	White, Black, Silver , color can be customized
VESA mounting	100×100mm
IP-grade	Full IP65
Operating Environment	
Temperature Range	operating: -10 to 60°C, storage :-20 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Packing Details	
Net weight	10kg
Gross weight	14kg
Product Dimension	37×39×9 cm
Packing size	58×29×52 cm
Accessories	Power adapter, embedded screws
Other	
Warranty	1 year warranty