



## Features:

1. Robust and durable, all-metal enclosure, sealing design, [full IP67 waterproof](#), [Sealed I/O with cable set included](#).
2. 15" Industrial LCD panel, [high brightness 1500 nits](#), [sunlight readable](#). Cover with 2MM AG glass for [vandalproof](#).
3. [Wide Temperature Range](#): operating: -20 to 70°C, storage: -30 to 80°C.
4. [Interfaces](#): 1\* [IP67 waterproof DC in](#) +1\* [IP67 waterproof Video in](#).
5. High performance mainboard, 7x24 continuous operation.

**Model:SL15W IP67**

## LCD panel

Panel size	15"
Resolution	1024*768
Aspect ratio	4:3
Support Color	16.7M colors
Brightness (cd/m <sup>2</sup> )	1500 nits, <a href="#">sunlight readable</a>
Contrast ratio	700:1
View angle	80°/80°/70°/70° (R/L/U/D)

## Singal Ports

BNC	1xBNC
-----	-------

## OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese etc.
Support OS	Windows XP, Windwows /7/8/10, Linux, Mac OS X, Android, ect.

## Power Supply

External Power Supply	AC 100-240V
Working voltage	DC 12V
Power consumption	25 W

## Enclosure

Material	aluminium alloy front bezel + High strength cold rolled steel back case
Color	Black, white, Silver, color can be customized
VESA mounting	75x75mm / 100x100 mm
IP-grade	<a href="#">Full IP67 waterproof</a>

Operating Environment	
Temperature Range	operating: -20 to 70°C, storage: -30 to 80°C
Relative humidity	operating: 10% to 90%, storage: 5% to 90%
Packing Details	
Net weight	4kg
Gross weight	5kg
Product Dimension	37.26×29.99×4.22cm
Packing size	47x43x18 cm
Accessories	Power adapter, IP67 waterproof power cord, IP67 waterproof BNC cable
Other	
Mounting (options)	1) wall brackets for wall-mounting, VESA 100×100 mm
	2) stable metal holder to support the monitor
Warranty	1 year warranty

