Sihovision®

SHENZHEN SHINHO ELECTRONIC TECHNOLOGY CO., LTD

Professional Industrial Panel PC manufacturer

Address: Room 622, Hongyi Building, No. 227, Fulian Area, Sanlian Community, Longhua District, Shenzhen, China. Web: www.sihovision.com Phone: +86 0755 23747569 Mobile: 0086 13798532807 Email: amy@sihovision.com







Features:

- 1. Full IP67 sealed stainless steel enclosure.
- 2. Including Water-Proof Military DTL-38999 series iii connectors, Sealed I/O with cable set included.
- 2. Industrial LCD panel, wide viewing angle, true color.
- 4. Brightness upto 1000 nits, sunlight readable.
- 5. Covered with 3mm AF glass, anti-fogging, anti-fingerprint.
- 5. High performance motherboard, 7x24 continuous operation.
- 6. Support jet washing.

٨	AhoN	I-SI 1	19_WS	IP67-M	ı

LCD panel					
Panel size	19"				
Resolution	1280*1024				
Aspect ratio	5:4				
Support Color	16.7M colors				
Brightness (cd/m²)	1000 cd/m², sunlight readable				
Contrast ratio	1000:1				
View angle	85°/85°/80°/80° (R/L/U/D)				
Customization	Covered Anti-fogging glass				
Signal Ports					
AV	Composite video (PAL & NTSC) Water-Proof Military DTL-38999 series iii connectors				
VGA	optional				
DVI	optional				
HDMI	optional				
Audio in/out	optional				
OSD in the front bezel					
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.				
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.				
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.				
Power Supply					
External Power Supply	AC 100 - 240V, 50-60Hz				
Working voltage	DC 12V Water-Proof Military DTL-38999 series iii connectors				
Power consumption	≤35W				
Enclosure					
Material	Stainless steel 304				
Color	Silver				
VESA mounting	100x100mm				
IP grade	Full IP67				

Operating Environment					
Temperature Range	operating: -30 to 85°C, storage: -30 to 85°C				
Relative humidity	lative humidity operating: 10% to 80%, storage: 5% to 90%				
Packing Details					
Net weight	8.35kg				
Gross weight	10kg/pc/Carton, 21.5KG/2pcs/Carton				
Product Dimension	44.6*37.4*6.0cm				
Packing size	size 53*47*18cm/pc/Carton, 55*36*48CM/2pcs/Carton				
Accessories	Accessories IP67 waterproof Power adapter, waterproof AV cables.				
Other					
	VESA mounting				
Mounting	embedded mounting screws (optional)				
	desk stand holder (optional)				
Warranty	1 year warranty				
Certificates	ertificates CE, FCC, RoHS				
	AV DCIEV 4.16 379.7 379.7 60 60 100 100 100 100 100 100				