



Features:

6 RS-232 serial ports

2x Intel i210/i211 Gigabit LAN

One-key restore, watchdog, diskless boot

Low power fanless

Industrial grade working temperature -20°C~60°C

All connectors on-board

Model: SM10-3

PC

CPU	Intel® Celeron J5005, 4 Cores, 4 Threads, Base 2.4GHz, Turbo 2.7GHz, Fanless
CPU Optional	Intel® Core i3-6157U, 2 Cores, 4 Threads, Base 2.4GHz, Turbo 2.7GHz, Fanless
Memory	J5005 1xDDR4L SODIMM, Max 8GB i3-6157U/7100U/8130U 1xDDR4L SODIMM, Max 16GB
Storage	1x MSATA 1x 2.5 inch SATA HDD/SSD
Display	1x HDMI, 1x VGA
Network	2x GbE RJ45 Intel i211/i210
I/O	4x USB3.0, 2x USB2.0, 2xLAN(GbE RJ45 Intel i211/i210), 6x COM (RS232), 1x HDMI, 1xVGA, 1x Power Button, 1x3.5mm Jack, 1x Mic in, 2x Antenna port, be used for WIFI/3G/4G
Expansion Slot	1x Mini-PCle half card, support WIFI Bluetooth 1x Mini-PCle full card (with SIM card holder), support 3G/4G module, WIFI Bluetooth
BIOS	AMI EFI BIOS
WDT	Support hardware reset (256 level, 0-255 sec)
Operation System	Windows® 7/8/10, WES 7/10, LINUX J4125 supports Windows® 10, WES 10, LINUX

Power Supply

External Power Supply	AC 100 - 240V
Working voltage	DC 12V
Power consumption	≤15W

Enclosure

Material	Aluminum Alloy
Color	White

Operating Environment	
Temperature Range	Operating: -20 to 60°C, Storage: -30 to 70°C, surface air flow
Relative humidity	10%~95% , non-condensing
Packing Details	
Net weight	1.0 kg
Gross weight	2.0 kg
Product Dimension	180 x 120 x 54 mm
Packing size	30*20*12cm
Accessories	Power adapter, Driver CD, 2.5-inch hard drive bracket, Screws
Other	
Mounting (options)	Wall mounting
	Embedded mount
Warranty	2 years warranty

